Sampling for Radon in Air Re-evaluation Testing for Compliance with Connecticut General Statute 10-220 (d)

Plainville High School 47 Robert Holcomb Way Plainville, Connecticut December 6, 2022 – December 8, 2022

Plainville Community Schools
Plainville, Connecticut

March 28, 2023

Eagle Environmental, Inc. 8 South Main Street Terryville, Connecticut (860) 589-8257



- Industrial Hygiene / IAQ
- Hazardous Building Materials
- > Environmental Assessments
- > Laboratory Services & Training

March 28, 2023

Mr. Michael Smith Facilities Director Plainville Community Schools 47 Robert Holcomb Way Plainville, Connecticut 06062

RE: Plainville Community Schools Radon Study:

5-Year Re-evaluation (December 6-8, 2022)

Plainville High School 47 Robert Holcomb Way Plainville, Connecticut Eagle Project No. 22-057

Eagle Project No. 22-057.13T5

Dear Mr. Smith:

Enclosed is the report for the 5-year re-evaluation testing for airborne radon conducted at Plainville High School at 47 Robert Holcomb Way in Plainville, Connecticut in compliance with Connecticut General Statute 10-220 (d). The sampling for this school was performed from December 6, 2022 to December 8, 2022. Notification of the results has been made to the State of Connecticut Department of Public Health and a copy of the State Notification Form is attached in Appendix B of this report.

If you have any questions regarding the contents of this report, please do not hesitate to contact us at (860) 589-8257. Thank you for this opportunity to serve your environmental needs.

Sincerely,

Eagle Environmental, Inc.

Report Written by:

Evan Kulig

Environmental Consultant I

Report Reviewed by:

Jason Eberhard

Senior Project Manager

Certified Radon Professional (Certification No. NRRP 111005 RMP)

Table of Contents

Report of Sampling for Radon in Air Re-evaluation Testing per Connecticut General Statute 10-220 (d) Plainville Community Schools

2.0	Rado	on Information and Sampling Procedures	1
	2.1	Radon Facts and Health Effects	
	2.2	Airborne Radon Sampling	
	2.3	Airborne Radon Quality Assurance Procedures	
3.0	Rado	on Analytical Results	3
	3.1	Spike Samples	
	3.2	School Re-Evaluation Samples	
4.0	Conc	lusion	5

Appendix A: Notification Letter to Parents and Staff

Appendix B: State of Connecticut Department of Public Health School Radon Re-Evaluation Report Form

Appendix C: Spike Sample Results and Chain-of-Custody Forms

Appendix D: Laboratory Results and Chain-of-Custody Forms

Appendix E: Eagle Environmental, Inc. Certificates

Appendix F: Laboratory Certificates

1.0 INTRODUCTION

Plainville Community Schools retained Eagle Environmental, Inc. (Eagle) to perform a radon measurement study utilizing passive airborne radon canisters at the Plainville High School located at 47 Robert Holcomb Way in Plainville, Connecticut. Eagle representative Evan Kulig performed the sampling from December 6, 2022 to December 8, 2022.

The sampling was performed under the supervision of Mr. Jason Eberhard. Mr. Eberhard received his initial radon training through CERTI's EPA-approved "Radon and Radon Decay Product Measurement Course" and received his accreditation in the National Radon Proficiency Program (NRPP) (Certificate #111005 RMP). He also completed the State of CTDPH Course "Radon Measurement in Connecticut Schools" on June 15, 2020. Copies of Mr. Eberhard's certificates are enclosed within Appendix E.

Plainville Community Schools performed initial radon testing in all existing schools from February 27th through March 1st, 2006 in response to the requirement of Connecticut General Statute Section 10-220 (d), also known as Indoor Air Quality (IAQ) in School Law. The sampling followed the protocols in the USEPA document: Radon Measurement in Schools, EPA 402-R-92-014, July 1993, and satisfied the requirements of the CTDPH as outlined in its "School Radon Testing Guidance" document.

This testing was a follow up study that is required every five (5) years after the initial test. CTDPH requires retesting of 10% of the rooms that were tested initially in a randomized fashion every five (5) years. In addition, all rooms that had radon concentrations in excess of 4.0 pCi/L requiring radon mitigation are required to be re-tested. Each successive five (5) year re-test must include a new set of 10% of rooms that were not tested earlier and each room with initial elevated radon level. Each round must include analysis of 10% "duplicate," 5% "blanks" and 3% "spike" samples, as required.

During the initial testing of Plainville High School, sixty-seven (67) samples were collected and no room had radon concentration in excess of 4.0pCi/L.

Eagle representative Melinda Rhode performed the last round of re-test sampling from November 13 through 16, 2017. Passive radon detection canisters were placed at nine (9) locations within the school building. In addition, one (1) "duplicate" sample and one (1) "blank" were placed. One (1) canister deployed in Room 122 had to be discarded because the canister was moved. The concentrations of radon in the samples ranged from 0.2 pCi/L to 1.0 pCi/L. All concentrations were below the USEPA action level of 4.0 pCi/L. Therefore, none of the previously tested locations were required for retesting.

2.0 RADON INFORMATION AND SAMPLING PROCEDURES

2.1 Radon Facts and Health Effects

Radon is a naturally-occurring radioactive gas produced by the natural breakdown (decay) of uranium which is found in soil and rock strata throughout the United States. Radon travels through soil and enters buildings through cracks and other penetrations in building foundations. Eventually the gas itself decays into radioactive particles (decay products) that can become trapped in the lungs during human respiration. As these particles in turn decay, they release small bursts of radiation which can damage lung tissue and lead to lung cancer over the course of a person's lifespan.

Like other environmental pollutants, there is some uncertainty about the magnitude of radon health risks. However, scientists are more certain about radon risks than risks from most other

cancer-causing environmental pollutants as estimates of radon risk are based on studies of cancer in humans (underground miners). USEPA estimates that radon may cause about 14,000 lung cancer deaths in the U.S. each year. The U.S. Surgeon General has warned that radon is the second-leading cause of lung cancer deaths after smoking, and is the leading cause of lung cancer among non-smokers.

USEPA studies have found that the radon concentration in outdoor air averages approximately 0.4 picoCuries per liter of air (pCi/L). However, radon and its decay products may accumulate within a building, generating much higher concentrations. The USEPA has adopted an Action Level of 4.0 pCi/L. USEPA recommends that school systems take measures to reduce the level of airborne radon in the areas where the concentration is equal to or greater than the Action Level.

Again, radon is a known human carcinogen. Prolonged exposure to elevated radon concentrations causes an increased risk of lung cancer. Radon is a colorless, odourless and tasteless gas. Thus, the only way to know whether or not an elevated level of radon is present in a building is to test.

2.2 Airborne Radon Sampling

On December 6, 2022, Eagle Representative Evan Kulig, under the supervision of Mr. Jason Eberhard Certified Radon Professional (Certification No. NRRP 111005 RMP), placed passive radon detection canisters at eight (8) locations within the school building. In addition, one (1) "duplicate" sample and one (1) "blank" sample were deployed. Eagle representative Evan Kulig then retrieved the canisters on December 8, 2022. To preserve the integrity of the sampling process, the identities of the "duplicate" and the "blank" samples were intentionally masked so the analytical laboratory could not distinguish them.

The canisters were supplied and analyzed by Radon Testing Corporation of America (RTCA). As recommended, canisters were placed in frequently occupied rooms within the lowest level of the school that is in contact with the ground. Canisters were not placed in hallways or rooms with high levels of moisture or heat, such as boiler rooms, bathrooms and locker rooms. In such cases, it is recommended that a canister be placed in a room directly above the area in order to assess the radon level. Also, the rooms that were tested in the 2017 retesting round were not tested again. Where possible, canisters were placed at least twenty (20) inches from the floor and three (3) feet away from exterior and interior walls and windows. Also, canisters were not placed near drafts resulting from HVAC intakes and returns or frequently opened doors. When possible, canisters were not exposed to direct sunlight, covered up, or otherwise disturbed during the testing period. A closed building condition was utilized for twelve (12) hours prior to testing being conducted. To comply with the regulatory requirements, canisters were deployed during the coldest months of the year (November through March) and during normal school days (Monday through Friday, excluding holidays and planned full-day closures).

The School Administration notified the parents and staff informing them of the radon testing program. Copies of the Notifications are attached as Appendix A.

2.3 Airborne Radon Quality Assurance Procedures

USEPA strongly recommends that quality assurance measurements are included in radon measurement studies. Quality assurance measurements include "spikes" (laboratory authentication), side by side canisters ("duplicates"), and unexposed control canisters ("blanks").

Spike Samples are used to determine the accuracy of the normal measurement process. For each month of active radon sampling, a batch of canisters provided by Eagle Environmental, Inc. is

exposed to a known and elevated concentration of radon gas (i.e., "spiked") at a secondary laboratory, separate from the primary laboratory used for analysis of the school samples. The "spike" samples thus exposed are sent as normal school samples to the primary laboratory. Upon receipt of the spike sample results from the primary laboratory, relative percent error (RPE) is calculated as follows:

$$RPE = \frac{\frac{\text{Target Value-Measured Value}}{\text{Target Value}}}{\text{Target Value}} \times 100\%$$

The results of analysis at the primary laboratory should have an average error of approximately + or -10% of the target value set by the secondary laboratory. The expectation is that the values of RPE fall between +10% and -10%, but the entire range of +20% to -20% is considered "in control." Outside of +/-20% but inside of +/-30% is the warning level and outside of +/-30% is the control limit. Any RPE outside of 20% should be investigated and documented. The number of spikes should be 3% of the detectors deployed during a month with a maximum of six (6) spikes per month.

Spike samples were prepared at Bowser-Morner, Inc., in Dayton, Ohio from December 5, 2022 through December 7, 2022 and submitted to RTCA on December 12, 2022. A fictitious site address and chain-of-custody form was created to hide the identity of the samples. Copies of chain-of-custodies and results are enclosed in Appendix C.

Duplicates are pairs of canisters deployed in the same location, side by side for the same measurement period. "Duplicates" are placed in at least 10% of all sampling locations up to a maximum of fifty (50) locations. These "duplicate" canisters are stored, deployed, removed, and shipped to the laboratory for analysis in the same manner as the other canisters. If either of the tests in a "duplicate" pairing is above the EPA standard of 4.0 pCi/L, as adjusted for canister error rate (see below), then the relative percent difference (RPD) between the two (2) tests must be determined as follows:

$$RPD = \frac{Initial Result-Duplicate Result}{Average of Both Results} x 100\%$$

If results that are over 4.0 pCi/L differ by 25% or more, the data quality should be questioned. If both canisters' results are below 4.0 pCi/L then the RPD is not calculated since, despite any disparity, both results are below the EPA standard.

Blanks are utilized to determine whether the manufacturing, shipping, storage, and processing of the canisters has affected the accuracy of airborne radon sampling procedures. "Blanks" are unexposed canisters which are shipped with the exposed canisters so that the processing laboratory cannot distinguish them. The number of "blanks" is at least 5% of the number of canisters deployed, up to a maximum of twenty-five (25) canisters.

3.0 RADON ANALYTICAL RESULTS

3.1 Spike Samples

In the summary table below are the results of the quality control spike tests.

TABLE 1: SPIKE SAMPLE RESULTS

CANISTER NUMBER	TARGET VALUE (pCi/Liter)	MEASURED VALUE (pCi/Liter)	ERROR (%)
3033173		31.3	16
3033217	37.3	36.5	2
3033212		42.9	15

The "spike" analysis was acceptable with an average error of 11%. The primary laboratory was confirmed suitable for analysis of the school re-evaluation samples. "Spike" sample chain-of-custodies and laboratory reports are attached as Appendix C.

3.2 School Re-Evaluation Samples

In the summary table below are the results of all samples placed in the school with their respective "blank" canisters, as described in the previous section. In addition, the results of all quality control "duplicate" tests, average radon level, and relative percent difference, if applicable, between the two (2) canisters are listed. Because Eagle created fictitious rooms, in order to satisfy requirements to disguise "blanks" and "duplicates," the table lists both the names designated on the chain-of-custody, as well as the actual sample identity.

TABLE 2: SCHOOL RE-EVALUATION SAMPLE RESULTS

FLOOR	FICTITIOUS ROOM NAME	ME SAMPLE LOCATION	CANISTER	RADON LEVEL (pCi/Liter)	
FLOOR	ON CHAIN OF CUSTODY		NUMBER	Sample	Duplicate Average
1 st Floor		Room 103-C	3034320	0.2	
1 st Floor		Room 115	3034274	0.1	
1 st Floor		Room 128	3034359	0.1	
1 st Floor		Room 102	3034269	0.1	
1 st Floor		Room 318	3034356	0.2	
1 st Floor	-	Room 311	3034299	0.4	
1st Floor	Room 324	Room 311 (Duplicate)	3034852	0.1	0.25
1 st Floor	1	Room 328	3034340	0.5	
1 st Floor		Room 333	3034343	0.8	
1 st Floor	Room 323	NA (Blank)	3023976	0.1	

The concentrations of radon in the samples ranged from 0.1 pCi/L to 0.8 pCi/L. All samples were below the USEPA action level of 4.0 pCi/L. The "blank" and "duplicate" analyses were acceptable. The RPD was not calculated, since in the "duplicate" pair, both results were below the 4.0 pCi/L standard, as adjusted for the canister error rate. Sampling chain-of-custodies and laboratory reports are attached as Appendix D.

4.0 CONCLUSION

During the course of the radon re-evaluation in the Plainville High School, ten (10) sampling canisters, including "duplicates" and "blanks," were placed at random locations distributed throughout the school. Sampling complied with all Connecticut Department of Public Health and USEPA requirements. The RPD was not calculated since in the "duplicate" pair, both results were below the 4.0 pCi/L standard, as adjusted for the canister error rate. The "blank" sampling canister did not exceed a level that would question the validity of the radon measurement study.

The average outdoor radon concentration as studied by the USEPA is 0.4 pCi/L and the average indoor concentration is 1.3 pCi/L. The USEPA has a recommended action guideline of 4.0 pCi/L and recommends taking further action (fixing the problem) if the results are over 4.0 pCi/L. The results for Plainville High School were all below the USEPA action level.

Notification of the results has been made to the State of Connecticut Department of Public Health and a copy of the State Notification Form is attached in Appendix B of this report.

APPENDIX A NOTIFICATION LETTER TO PARENTS AND STAFF

Date: 11/4/2022

School: Plainville Community School District

Address: 47 Robert Holcomb Way Plainville CT 06062

Dear Parents and Staff:

The administration of Plainville Community Schools would like to notify you that radon testing will be conducted at all schools in the district. According to Connecticut General Statute Sec. 10-220(d), all public schools must inspect and evaluate the indoor air quality in school buildings every five years. This required inspection and re-evaluation of indoor air quality includes evaluation of radon gas.

The purpose of the re-evaluation of indoor air quality is to determine if air quality has changed in the past five years.

Eagle Environmental, Inc. will conduct the five-year radon re-evaluation of the school buildings. To re-evaluate buildings for radon in air, a limited number of locations are selected. Small test devices containing charcoal will be placed in ten percent of the occupied rooms that are in contact with the ground. (In addition, devices will be placed in all previously mitigated rooms. That is, rooms where radon was reduced by the installation of a radon mitigation system.) Radon test devices are safe and do not cause any adverse health effects. These devices will be left in place for two to three school days.

The school administration will keep radon test reports on file and inform you of test results and interpretations when all testing has been completed. If elevated levels of radon are found, steps will be taken to reduce radon levels below the United States Environmental Protection Agency action level of 4.0 pCi/L.

If you have any concerns regarding radon testing, please feel free to contact your school's radon testing professional or the State of Connecticut Department of Public Health Radon Program at (860) 509-7367 or visit the website:

https://portal.ct.gov/-/media/Departments-and-Agencies/DPH/dph/environmental_health/radon/2021/EPA_School-Pamphlet.pdf

Sincerely,

Superintendent of Schools

APPENDIX B

STATE OF CONNECTICUT DEPARTMENT OF PUBLIC HEALTH SCHOOL RADON RE-EVALUATION REPORT FORM



STATE OF CONNECTICUT

DEPARTMENT OF PUBLIC HEALTH RADON PROGRAM SCHOOL RADON **RE-EVALUATION** REPORT FORM

January 2021

The following form must be submitted to the Connecticut Department of Public Health Radon Program within ten (10) business days of providing a final written report of radon measurement activities to school personnel. **Do not send test results or other documents**. Submit only one signed form by **mail, fax** OR **email (preferred)** to the Radon Program at:

CT Department of Public Health Radon Program 410 Capitol Avenue MS#12RAD Hartford, CT 06134-0308 Fax: 860-509-7295

Email: DPH.RadonReports@ct.gov

Name of School:	Plainville High School				
Address:	47 Robert Holcomb Way				
(Street, town, zip code)	Plainville				
	06062				
Measurement Company:	Eagle Environmental, Inc.				
Please provide the following summar	y information:				
Testing Dates: (deployment & retrieval. Include confirmatory	December 6, 2022 - December 8, 2022				
testing dates if necessary)					
Total # of Rooms Tested:	8				
Total # of Rooms Requiring Re-Testing:	0				
Total # of Rooms Where Average Results were at or above 4.0 pCi/L:	0				
P C C	<u> </u>				
	formed at the location above in accordance with United cols and the Connecticut Department of Public Health Ince.				
Jason Eberhard/NRPP # 111	005 Jun Muband	2/15/2023			
Measurement Professional / NRPP/NRS	B# Signature	Date			
Michael Smith School Designee / Title	Mul Al-	2 14 23 Date			
<u> </u>	- (0.40) - 0.0 - 0.00				



Phone: (860) 509-7300
Telephone Device for the Deaf (860) 509-7191
450 Capitol Avenue - MS # 51RAD
P.O. Box 340308 Hartford, CT 06134
An Equal Opportunity Employer

APPENDIX C SPIKE SAMPLE RESULTS AND CHAIN-OF-CUSTODY FORMS

Radon Testing Corp. of America

2 Hayes Street, Elmsford, NY 10523, Phone: (914)345-3380

Radon Testing Summary Sheet Please fill out all pertinent information legibly

Send Results Report to: Contact: bleblanc @ eagle enviro. com, Vfar Eas @ eagle enviro. com
Company/Agency/Board of Ed: <u>Eagle Environ weator</u>
· · · · · · · · · · · · · · · · · · ·
Address: B South Main Street, Suite 3
City: Tarry ville State: CT Zip:
Phone: <u>860-589-8257</u> Fax:
Email:
School District: First Class Realty School Code #:
County: Municipality:
Building/School Name: The Front Stroet Building
Address: 21 Front Street
City: Bristol State: CT Zip:
Placed by ID#: Retrieved by ID#:
Start Date: 12/5/22 Stop Date: 12/7/22
Time zone: Total # of detectors for this building: $oldsymbol{\mathcal{Z}}$
DI FACE CIDGLE ADDRODRIATE CONDITIONS
PLEASE CIRCLE APPROPRIATE CONDITIONS Building Type: Day Care-(D) Residential-(R) Non-Residential-(N)
School-(S) Public School-(P) Unknown-(U)
Structural Type of Building: Basement-(B) Prawlspace-(C) Slab-on-grade-(S) Other-(O) Unknown-(U)
Purpose of Test: Screening-(S) Real Estate-(R) Post Mitigation-(POM)
Test Conditions: Open House-(OH) Closed House-(CH) Rainy-(RA) Windy-(WY) Unknown-(NO)

location and indicate	of center bar coded label from determined bar code label is left on detector. if QA measurement for each determined from detector is missing or damagners.	Record star ctor. Use add	t & stop time, ide: ditional sheets as i	ntify test	
Bar Code Label	Start Time:	Stop Time:	11:24		
TO TEST INFORMATION FORM 3033217	Room # or other identifier:	sement _{te}	Floor: B		
1 138188 11111 88188 11118 11118 11181 1181 1181 1	Please circle if QA Measurement:	Blank	Duplicate		
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM 3033173	Start Time: Bound Proced Carl				
	Room # or other identifier: baseauch	+ Ram 1 - Ce	wfarFloor: B		
	Please circle if QA Measurement:	Blank 			
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM	Start Time: 12/5/22	Stop Time: _	11:24	12/7/22	JE
3033212	Room # or other identifier:	f Roem 1 - k	Right Floor: B		
(IRRIAR IIII RAIRA IIIR	Please circle if QA Measurement:	Blank	Duplicate		
	Start Time:	Stop Time: _			
	Room # or other identifier:		Floor:		
·	Please circle if QA Measurement:	Blank	Duplicate		
	Start Time:	Stop Time: _			
	Room # or other identifier:	_	Floor:	-	
	Please circle if QA Measurement:	Blank	Duplicate		
	Start Time:	Stop Time: _			
	Room # or other identifier:		Floor:		
3 .	Please circle if OA Measurement	Dlank	Doublest		

Page _____ of _____

EXPOSURE IN BOWSER-MORNER RADON CHAMBER

CLIENT <u>Eagle Environmenta</u>	1, Inc. Job Number 2080>9
NOMINAL Conditions: Radon Conc 37.3	pCi/L Rel. Hum 49.7 % Temp. 69.6 F
Date Start: 12/5/12 Date Stop: 12/7/22	Date Start: Date Stop:
Time Start: Time Stop: 1124	Time Start: Time Stop:
Device No.'s: 3033173,	Device No.'s:
3033212, 3033217	
Date Start: Date Stop:	Date Start: Date Stop:
Time Start: Time Stop:	Time Start: Time Stop:
Device No.'s:	Device No.'s:
-	
Date Start: Date Stop:	Date Start: Date Stop:
Time Start: Time Stop:	Time Start: Time Stop:
Device No.'s:	Device No.'s:
	· · ·

Note: All times are in 24-hour (military) notation, Eastern Standard Time (EST) Background = $7 \mu R/h$ Elevation = 820 ft



Site Radon Inspection Report

Ms. Brandy LeBlanc-Christen EAGLE ENVIRONMENTAL 8 South Main Street Suite 3 Terryville, CT 06786-

Client: The Front Street Bldg. Test Location: 21 Front Street

Bristol, CT

Individual Canister Results

 Canister ID#:
 3033173
 Test Start:
 12/05/2022 @ 11:24

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/07/2022 @ 11:24

 Location:
 Bsmt=Ctr Rm 1
 Received:
 12/12/2022 @ 14:29

 Radon Level:
 31.3 pCi/L
 Analyzed:
 12/12/2022 @ 16:18

Error for Measurement is: ± 0.9 pCi/L

 Canister ID#:
 3033217
 Test Start:
 12/05/2022 @ 11:24

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/07/2022 @ 11:24

 Location:
 Bsmt=Left Rm 1
 Received:
 12/12/2022 @ 14:29

 Radon Level:
 36.5 pCi/L
 Analyzed:
 12/12/2022 @ 16:18

Error for Measurement is: ± 1.0 pCi/L

 Canister ID#:
 3033212
 Test Start:
 12/05/2022 @ 11:24

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/07/2022 @ 11:24

 Location:
 Bsmt=Right Rm 1
 Received:
 12/12/2022 @ 14:29

 Radon Level:
 42.9 pCi/L
 Analyzed:
 12/12/2022 @ 16:18

Error for Measurement is: ± 1.1 pCi/L

The results indicate that at least one testing device registered at or above the United States Environmental Protection Agency (EPA) action level of 4.0 picoCuries per liter of air (pCi/L). The EPA recommends mitigation if the average of two short-term tests taken in the lowest level of the building suitable for occupancy show radon levels that are equal to or greater than 4.0 pCi/L.

For information on how to reduce radon levels in your home, please review the EPA booklet: Consumer's Guide to Radon Reduction (www.epa.gov/radon/pdfs/consguid.pdf) and contact your state health department. The EPA maintains a radon information website, including copies of its publications, at www.epa.gov/iaq/radon.

For New Jersey clients: Please see the attached guidance document entitled <u>Radon Testing and Mitigation: The</u> Basics for further information.

For New York clients: If the radon level of one or more testing devices is equal to or exceeds 20 pCi/L please contact the New York State Department of Health, Bureau of Environmental Radiation Protection, for technical advice and assistance at 518-402-7556 or toll free 1-800-458-1158.



Andrews C. George

Andreas C. George
Radon Measurement Specialist

Dante Galan Laboratory Director



Site Radon Inspection Report

Ms. Brandy LeBlanc-Christen EAGLE ENVIRONMENTAL 8 South Main Street Suite 3 Terryville, CT 06786-

Client: The Front Street Bldg. Test Location: 21 Front Street

Bristol, CT

Individual Canister Results

PLEDGE OF ASSURED QUALITY

All procedures used for generating this report are in complete accordance with the current EPA protocols for the analysis of radon in air (EPA 402-R-92-004). The analytical results relate only to the samples tested, in the condition received by the lab, and that calculations were based upon the information supplied by client. RTCA and its personnel do not assume responsibility or liability, collectively and individually, for analysis results when detectors have been improperly handled or placed by the consumer, nor does RTCA and its personnel accept responsibility for any financial or health consequences of subsequent action or lack of action, taken by the customer or it's consultants based on RTCA-provided results.



Andrews C. George

Andreas C. George Radon Measurement Specialist Dante Galan Laboratory Director

APPENDIX D LABORATORY RESULTS AND CHAIN-OF-CUSTODY FORMS

Radon Testing Corp. of America

2 Hayes Street, Elmsford, NY 10523, Phone: (914)345-3380

Radon Testing Summary Sheet Please fill out all pertinent information legibly

Send Results Report to: Contact: Bleblanc @ Pagle Puviro . Com, V faukas @ Pagle enviro. Com
Company/Agency/Board of Ed: <u>Eagle Environmental Inc.</u>
Address: 8 South Main Street, Suite 3
City: Terry ville State: CT Zip: 06789
Phone: Fax:
Email:
School District: Plainville Community School Code #:
County: Municipality:
Building/School Name: Plainville High School
Address: 47 Robert Holcomb Way
City: Plain Ville State: CT Zip:
Placed by ID#: EK Retrieved by ID#: EK
Start Date: 12/6/2022 Stop Date: 12/8/2022
Time zone: Total # of detectors for this building:
PLEASE CIRCLE APPROPRIATE CONDITIONS
Building Type: Day Care-(D) Residential-(R) Non-Residential-(N) School-(S) Public School-(P) Unknown-(U)
Structural Type of Building: Basement-(B) Crawlspace-(C) Slab-on-grade-(S) Other-(O) Unknown-(U)
Purpose of Test: Screening-(S) Real Estate-(R) Post Mitigation-(POM)
Test Conditions: Open House-(OH) Closed House-(CH) Rainy-(RA) Windy-(WY) Unknown-(NO)

Page	. /	of	7	2
1 450_		_ 🖰	· /	

Instructions: Tear off center bar coded label from detector and affix to sheet in spaces provided. Please make sure top bar code label is left on detector. Record start & stop time, identify test location and indicate if QA measurement for each detector. Use additional sheets as necessary. Please mark clearly if any detector is missing or damaged at retrieval.

12/6/22

12/9/22

Bar Code Label

	12/6/22 12/8/22	_
Bar Code Label	Start Time: 14:25 Stop Time: 15:13	
TO TEST INFORMATION FORM 3034320	Room # or other identifier: 103 C Floor: 1	
	Please circle if QA Measurement: Blank Duplicate	,
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM	Start Time: 14:31 Stop Time: 15:18	
3034274	Room # or other identifier:Floor:	
	Please circle if QA Measurement: Blank . Duplicate	
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM 3034359	Start Time: $\frac{\frac{12}{6}/22}{\frac{14}{35}}$ Stop Time: $\frac{\cancel{5}\cancel{15}}{\cancel{5}\cancel{5}}$	12/8/22
	Room # or other identifier: 128 Floor: 1	
	Please circle if QA Measurement: Blank Duplicate	
REMOVE THIS PORTION AND AFFIX	12/6/22 12/8/2 Start Time: /4:40 Stop Time: /5:16	2
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM 3034269	12/0/2	•
TO TEST INFORMATION FORM	Start Time: 14:40 Stop Time: 15:16	•
TO TEST INFORMATION FORM	Start Time: 14:40 Stop Time: 15:16 Room # or other identifier: 102 Floor: 1	
TO TEST INFORMATION FORM 3034269	Start Time: $/4.40$ Stop Time: $/5.16$ Room # or other identifier: $/02$ Floor: $/16$ Please circle if QA Measurement: Blank Duplicate	
REMOVE THIS FORMATION FORM	Start Time: 19.90 Stop Time: 15.16 Room # or other identifier: 102 Floor: 15.16 Please circle if QA Measurement: Blank Duplicate $12/6/22$ $12/6/2$ Start Time: 19.92 Stop Time: 15.27	
REMOVE THIS FORTION AND AFFIX	Start Time: $/9.90$ Stop Time: $/5.16$ Room # or other identifier: $/02$ Floor: $/16$ Please circle if QA Measurement: Blank Duplicate $/2/6/22$ $/2/6/2$ Start Time: $/9.90$ Stop Time: $/9.90$ Room # or other identifier: $/9.90$ Floor: $/9.90$	
REMOVE THIS FORMATION FORM 3034269 TO TEST INFORMATION FORM 3034356	Start Time: 99.90 Stop Time: 99.16 Room # or other identifier: 99.16 Floor: 99.16 Please circle if QA Measurement: Blank Duplicate Start Time: 99.16 Stop Time: 99.16 Floor: 99.16 Room # or other identifier: 99.16 Stop Time: 99.16 Floor: 99.16 Please circle if QA Measurement: Blank Duplicate	

Page_	. 2	_of	12

Instructions: Tear off center bar coded label from detector and affix to sheet in spaces provided. Please make sure top bar code label is left on detector. Record start & stop time, identify test location and indicate if QA measurement for each detector. Use additional sheets as necessary. Please mark clearly if any detector is missing or damaged at retrieval.

70 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	12/6/22		12/8/	/22
Bar Code Label	Start Time: /4:52	Stop Time:	15:25	
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM 3034852	Room # or other identifier: 3			1
1 184144 HIII 84144 HIII 8484 1844 8114 114 116	Please circle if QA Measurement:	Blank	Duplicate	
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM	Start Time: 14:55	Stop Time: _	15:29	8/22
3034340	Room # or other identifier: 32	28	Floor:	
	Please circle if QA Measurement:	Blank .	Duplicate	
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM	72/6/22 Start Time: 14:58	Stop Time: _	12/8/	2 2
3034343	Room # or other identifier:3	33	Floor:	1
	Please circle if QA Measurement:			•
REMOVE THIS PORTION AND AFFIX TO TEST INFORMATION FORM	12/6/22 Start Time: 15:03	Stop Time: _	12/61	22
3023976	Room # or other identifier: 3	23	Floor:	1
	Please circle if QA Measurement:	Blank	Duplicate 	
	Start Time:	Stop Time: _		
	Room # or other identifier:		Floor:	
	Please circle if QA Measurement:	Blank	Duplicate	
	Start Time:	Stop Time: _		
	Room # or other identifier:		Floor:	
t,	Please circle if QA Measurement:	Blank	Duplicate	



Site Radon Inspection Report

Ms. Brandy LeBlanc-Christen EAGLE ENVIRONMENTAL 8 South Main Street Suite 3 Terryville, CT 06786-

Client: Plainville H.S.

Test Location: 47 Robert Holcomb Way

Plainville, CT 06062-

Individual Canister Results

 Canister ID#:
 3034320
 Test Start:
 12/06/2022 @ 14:25

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:13

 Location:
 1st FL=Rm 103-C
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.2 pCi/L
 Analyzed:
 12/12/2022 @ 16:37

Error for Measurement is: ± 0.3 pCi/L

 Canister ID#:
 3034274
 Test Start:
 12/06/2022 @ 14:31

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:18

 Location:
 1st FL=Rm 115
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.1 pCi/L
 Analyzed:
 12/12/2022 @ 16:37

Error for Measurement is: ± 0.2 pCi/L

 Canister ID#:
 3034359
 Test Start:
 12/06/2022 @ 14:35

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:19

 Location:
 1st FL=Rm 128
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.1 pCi/L
 Analyzed:
 12/12/2022 @ 16:44

Error for Measurement is: ± 0.7 pCi/L

 Canister ID# :
 3034269
 Test Start :
 12/06/2022 @ 14:40

 Canister Type :
 Charcoal Canister 3 inch
 Test Stop :
 12/08/2022 @ 15:16

 Location :
 1st FL=Rm 102
 Received:
 12/12/2022 @ 14:31

 Radon Level :
 0.1 pCi/L
 Analyzed:
 12/12/2022 @ 16:19

Error for Measurement is: ± 0.5 pCi/L

Canister ID#: 3034356 Test Start: 12/06/2022 @ 14:45
Canister Type: Charcoal Canister 3 inch Test Stop: 12/08/2022 @ 15:27

Location: 1st FL=Rm 318 Received: 12/12/2022 @ 14:31 Radon Level: 0.2 pCi/L Analyzed: 12/12/2022 @ 16:37

Error for Measurement is: ± 0.4 pCi/L

 Canister ID#:
 3034299
 Test Start:
 12/06/2022 @ 14:50

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:25

 Location:
 1st FL=Rm 311
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.4 pCi/L
 Analyzed:
 12/12/2022 @ 16:37

Error for Measurement is: ± 0.4 pCi/L



Andrews C. George

Andreas C. George Dante Galan
Radon Measurement Specialist Laboratory Director

NJ MES 11089



Site Radon Inspection Report

Ms. Brandy LeBlanc-Christen EAGLE ENVIRONMENTAL 8 South Main Street Suite 3 Terryville, CT 06786-

Client: Plainville H.S.

Test Location: 47 Robert Holcomb Way

Plainville, CT 06062-

Individual Canister Results

 Canister ID#:
 3034852
 Test Start:
 12/06/2022 @ 14:52

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:25

 Location:
 1st FL=Rm 324
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.1 pCi/L
 Analyzed:
 12/12/2022 @ 16:19

Error for Measurement is: ± 0.3 pCi/L

 Canister ID#:
 3034340
 Test Start:
 12/06/2022 @ 14:55

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:29

 Location:
 1st FL=Rm 328
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.5 pCi/L
 Analyzed:
 12/12/2022 @ 16:44

Error for Measurement is: ± 0.3 pCi/L

 Canister ID#:
 3034343
 Test Start:
 12/06/2022 @ 14:58

 Canister Type:
 Charcoal Canister 3 inch
 Test Stop:
 12/08/2022 @ 15:31

 Location:
 1st FL=Rm 333
 Received:
 12/12/2022 @ 14:31

 Radon Level:
 0.8 pCi/L
 Analyzed:
 12/12/2022 @ 16:39

Error for Measurement is: ± 0.4 pCi/L

 Canister ID# :
 3023976
 Test Start :
 12/06/2022 @ 15:03

 Canister Type :
 Charcoal Canister 3 inch
 Test Stop :
 12/08/2022 @ 15:08

 Location :
 1st FL=Rm 323
 Received:
 12/12/2022 @ 14:31

 Radon Level :
 0.1 pCi/L
 Analyzed:
 12/12/2022 @ 15:59

Error for Measurement is: ± 0.5 pCi/L



Andrews C. George

Andreas C. George Radon Measurement Specialist Dante Galan Laboratory Director



Site Radon Inspection Report

Ms. Brandy LeBlanc-Christen EAGLE ENVIRONMENTAL 8 South Main Street Suite 3 Terryville, CT 06786-

Client: Plainville H.S.

Test Location: 47 Robert Holcomb Way

Plainville, CT 06062-

Individual Canister Results

The reported results indicate that radon levels in the building tested are below the United States Environmental Protection Agency (EPA) action level of 4.0 picoCuries per liter of air (pCi/L). The EPA recommends retesting if your living patterns change and you begin occupying a lower level of the building, such as a basement or if major remodeling is done.

General radon information may be obtained by consulting the EPA booklet: A Citizen's Guide to Radon (www.epa.gov/radon/pubs/citguide.html). To request a copy or for further information, please contact your state health department. The EPA maintains a radon information website, including copies of its publications, at www.epa.gov/iaq/radon.

For New Jersey clients: Please see the attached guidance document entitled <u>Radon Testing and Mitigation: The Basics</u> for further information.

For New York clients: If the radon level of one or more testing devices is equal to or exceeds 20 pCi/L please contact the New York State Department of Health, Bureau of Environmental Radiation Protection, for technical advice and assistance at 518-402-7556 or toll free1-800-458-1158.

PLEDGE OF ASSURED QUALITY

All procedures used for generating this report are in complete accordance with the current EPA protocols for the analysis of radon in air (EPA 402-R-92-004). The analytical results relate only to the samples tested, in the condition received by the lab, and that calculations were based upon the information supplied by client. RTCA and its personnel do not assume responsibility or liability, collectively and individually, for analysis results when detectors have been improperly handled or placed by the consumer, nor does RTCA and its personnel accept responsibility for any financial or health consequences of subsequent action or lack of action, taken by the customer or it's consultants based on RTCA-provided results.



Andrews C. George

Andreas C. George
Radon Measurement Specialist

Dante Galan Laboratory Director

APPENDIX E EAGLE ENVIRONMENTAL, INC. CERTIFICATES



Jason Eberhard



Has satisfactorily fulfilled the requirements set forth by the National Radon Proficiency Program and is therefore certified as a:

Radon Measurement Professional

with Standard Services

NRPP ID 111005-RMP Issued On: 2021-12-08 Expires: 2023-12-31

Valid for specific activities or measurement devices, which can be verified with NRPP. State and local agencies may have additional requirements.



In witness Whereof,
I have subscribed my name as a
Representative of NRPP

Christina Johnson

Christina Johnson NRPP Credentialing Manager

APPENDIX F LABORATORY CERTIFICATES

THE NATIONAL RADON SAFETY BOARD

Certified Radon Professionals

Certifies that

Radon testing Corporation of America, Inc. (RTCA,

2 Hayes Street, Elmsford, NY 10523

Has Successfully Met The Established & Published Requirements for Accreditation by The National Radon Safety Board as an

Accredited Radon Laboratory

ARL0001

Certification Number

11/30/2023

Expiration Date



Kehaulani Kekoa Certification Coordinator



This certificate is the property of The National Radon Safety Board